

MATERIAL SAFETY DATA SHEET

SECTION I: IDENTIFICATION OF PRODUCT

COMPANY: **Diversity Technologies Corp.** DATE: **March 3, 2011**
8750 – 53rd Ave. PHONE: 780-468-4064
Edmonton, AB T6E 5G2 FAX: 780-469-1899

PRODUCT NAME: **CSDS 120**

PRODUCT USE: Viscosifier and clay stabilizer for diamond core drilling.
CHEMICAL FAMILY: Anionic water soluble polymer CAS # Mixture

WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS)

WHMIS CLASSIFICATION: Not WHMIS controlled.
WORKPLACE HAZARD: May cause skin and eye irritation.

TRANSPORTATION OF DANGEROUS GOODS (TDG)

PROPER SHIPPING NAME: Not regulated under TDG
TDG CLASSIFICATION: Not applicable
UN NUMBER (PIN): Not applicable
PACKING GROUP: Not applicable

SECTION II: HAZARDOUS INGREDIENTS

<u>INGREDIENT</u>	<u>% (w/w)</u>	<u>CAS NUMBER</u>	<u>LD₅₀Oral-Rat</u>	<u>LC₅₀Inhal-Rat</u>	<u>ACGIH-TLV</u>
-------------------	----------------	-------------------	--------------------------------	---------------------------------	------------------

Contains no WHMIS controlled ingredients.

SECTION III: HEALTH HAZARDS

ROUTE OF ENTRY: [XX] EYE CONTACT [XX] SKIN [] INHALATION [XX] INGESTION
EYE CONTACT: Contact with liquid may cause eye irritation.
SKIN CONTACT: Contact with liquid may cause irritation. Prolonged contact may cause defatting of skin resulting in dermatitis.
INGESTION: May cause nausea and vomiting. LD₅₀ Oral Rat > 5000 mg/kg.
INHALATION: Vapours and mists may irritate the upper respiratory tract.
CARCINOGENICITY: No information available.
TERATOGENICITY: No information available.
REPRODUCTIVE TOXICITY: No information available.
MUTAGENICITY: No information available.

SYNERGISTIC PRODUCTS: No information available.

SECTION IV: FIRST AID MEASURES

SKIN CONTACT: Remove contaminated clothing, wash exposed area thoroughly with soap and water. If irritation persists, obtain medical attention.

EYE CONTACT: Immediately flush eyes with gently flowing warm water for 15 minutes, or until irritation ceases. If irritation persists, obtain medical attention.

INGESTION: Do not induce vomiting. If patient is fully conscious give 2 to 4 glasses of water. If vomiting occurs, keep head below hips to ensure vomitus is not aspirated. If symptoms develop, obtain medical attention. Never give anything by mouth to an unconscious or convulsing victim.

INHALATION: Move patient to fresh air. Apply oxygen or artificial respiration if required. If breathing difficulties or distress continues, obtain medical attention.

SECTION V: PHYSICAL DATA

APPEARANCE AND ODOUR:	Milky, viscous liquid; aliphatic odour
SPECIFIC GRAVITY:	1.02 – 1.05
BOILING POINT (°C):	Not available
MELTING POINT (°C):	Not available
SOLUBILITY IN WATER:	Not available pH: 6.5-7.5 (1% sol'n)
PERCENT VOLATILE BY VOLUME:	Not available
EVAPORATION RATE:	Not available
VAPOUR PRESSURE (mmHg):	0.002 @ 20°C
VAPOUR DENSITY (air = 1):	Not available
BULK DENSITY:	Not applicable

SECTION VI: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT:	>100°C
FLAMMABLE LIMITS:	Not available
EXTINGUISHING MEDIA:	Water spray, foam, dry chemical, carbon dioxide
SPECIAL FIRE FIGHTING PROCEDURES:	Self-contained breathing apparatus required for fire fighting personnel. Remove containers from fire area, or cool with water spray, if possible.
UNUSUAL FIRE AND EXPLOSION HAZARDS:	Material becomes very slippery when contacted by water.

SECTION VII: REACTIVITY DATA

STABILITY:	STABLE [XX]	UNSTABLE []
INCOMPATIBILITY (CONDITIONS TO AVOID):	Oxidizing agents may cause exothermic reactions.	
CONDITIONS OF REACTIVITY:	Not available	
HAZARDOUS DECOMPOSITION PRODUCTS:	Thermal decomposition may produce oxides of carbon and oxides of nitrogen.	
HAZARDOUS POLYMERIZATION:	WILL NOT OCCUR [XX]	MAY OCCUR []

SECTION VIII: PREVENTATIVE MEASURES**SPECIAL PROTECTION INFORMATION**

RESPIRATORY PROTECTION:	In case of insufficient ventilation and/or misty conditions, wear NIOSH approved respirator with dust/mist filters.
VENTILATION:	Natural ventilation is adequate in absence of mists. Use process enclosure, local exhaust ventilation or other engineering controls if misting occurs.
PROTECTIVE GLOVES:	Suggest rubber or viton.
EYE PROTECTION:	Suggest safety glasses with side-shields, chemical goggles and/or face shield. Do not wear contact lenses.
OTHER PROTECTIVE EQUIPMENT (Specify):	Suggest rubber apron. Ensure eye wash station and safety shower are available.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Avoid contact with skin and eyes. Use with adequate ventilation. Wash thoroughly after handling and before breaks. Launder contaminated clothing before reuse. Store in a cool, dry area away from oxidizers. Store between 0°C and 30°C. Freezing will affect the physical condition and may damage the material. This product has a shelf-life of six (6) months and stock should be rotated accordingly.

STEPS TO BE TAKEN IN CASE THE MATERIAL IS SPILLED OR RELEASED

Wear appropriate safety equipment. Dike to prevent spread of material. For large spills, collect by vacuum. For small spills, soak up with absorbent. Collect absorbent in approved containers for disposal. Wash spill area thoroughly with a bleach solution. Do not allow material to enter public waterways or storm sewer.

WASTE DISPOSAL METHOD

Dispose in accordance with federal, provincial and local regulations. It is the responsibility of the end-user to determine if material meets the criteria of hazardous waste at the time of disposal. Empty containers must be disposed of, or recycled, in accordance with local regulations.

SECTION IX: PREPARATION

THE INFORMATION CONTAINED HEREIN IS GIVEN IN GOOD FAITH,
BUT NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE.

DATE ISSUED: **March 3, 2011** BY: Product safety committee
SUPERSEDES: **March 1, 2008** PHONE: 780-440-4923

**Diversity Technologies Corp. is the parent company of
Canamara-United Supply, Hollimex Products, The Drilling Depot and
Westcoast Drilling Supplies.**