

MATERIAL SAFETY DATA SHEET

SECTION I: IDENTIFICATION OF PRODUCT

COMPANY: **Diversity Technologies Corp.** DATE: **January 26, 2011**
8750 – 53rd Ave. PHONE: 780-468-4064
Edmonton, AB T6E 5G2 FAX: 780-469-1899

PRODUCT NAME: **Grout-Well & Grout-Well DF**

PRODUCT USE: Oil well drilling fluid additive.
CHEMICAL FAMILY: Natural mineral, Montmorillonite CAS#: 1302-78-9

WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS)

WHMIS CLASSIFICATION: D2A
WORKPLACE HAZARD: Potential carcinogen; contains free silica.

TRANSPORTATION OF DANGEROUS GOODS (TDG)

PROPER SHIPPING NAME: Not regulated under TDG
TDG CLASSIFICATION: Not applicable
UN NUMBER (PIN): Not applicable
PACKING GROUP: Not applicable

SECTION II: HAZARDOUS INGREDIENTS

<u>INGREDIENT</u>	<u>% (w/w)</u>	<u>CAS NUMBER</u>	<u>LD₅₀Oral-Rat</u>	<u>LC₅₀Inhal-Rat</u>	<u>ACGIH-TLV</u>
Silica, crystalline quartz	1-5 or 5-10*	14808-60-7	Not available	Not available	0.025 mg/m ³ (respirable)

**The typical quartz content of western bentonite is between 2 and 6%.*

SECTION III: HEALTH HAZARDS

ROUTE OF ENTRY: []EYE CONTACT []SKIN [XX]INHALATION []INGESTION
EYE CONTACT: May cause mechanical irritation.
SKIN CONTACT: Possible drying resulting in dermatitis.
INGESTION: No adverse effects expected.

SECTION VI: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT:	Not applicable
FLAMMABLE LIMITS:	Not applicable
EXTINGUISHING MEDIA:	Use media suitable for surrounding fire and packaging.
SPECIAL FIRE FIGHTING PROCEDURES:	Self-contained breathing apparatus required for fire fighting personnel.
UNUSUAL FIRE AND EXPLOSION HAZARDS:	Product becomes very slippery when wet, avoid using water as fire fighting agent.

SECTION VII: REACTIVITY DATA

STABILITY:	STABLE [XX]	UNSTABLE []
INCOMPATIBILITY (CONDITIONS TO AVOID):	None known.	
CONDITIONS OF REACTIVITY:	Not available.	
HAZARDOUS DECOMPOSITION PRODUCTS:	None known.	
HAZARDOUS POLYMERIZATION:	WILL NOT OCCUR [XX]	MAY OCCUR []

SECTION VIII: PREVENTATIVE MEASURES**SPECIAL PROTECTION INFORMATION**

RESPIRATORY PROTECTION:	NIOSH/MESA approved respirators for silica bearing dust.
VENTILATION:	Use local exhaust ventilation, process enclosure or other engineering controls to maintain concentration of airborne dust below TLV.
PROTECTIVE GLOVES:	Generally not necessary; personal preference.
EYE PROTECTION:	Suggest goggles or safety glasses.
OTHER PROTECTIVE EQUIPMENT (Specify):	Ensure emergency eye wash station and safety shower are available.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Avoid creating dust. Avoid breathing dust; wear an approved respirator. Practice reasonable caution and personal cleanliness. Avoid eye contact. Store in cool, dry area. Empty packages contain residual hazardous material; handle as if full.

STEPS TO BE TAKEN IN CASE THE MATERIAL IS SPILLED OR RELEASED

Wear an approved respirator. Vacuum if possible to avoid generating airborne dust. Collect uncontaminated material for repackaging. Collect contaminated material in an approved container for disposal. Avoid adding water; the product will become slippery when wet.

WASTE DISPOSAL METHOD

Dispose in accordance with federal, provincial and local regulations. It is the responsibility of the end-user to determine if material meets the criteria of hazardous waste at the time of disposal. Empty packaging must be disposed of, or recycled, in accordance with local regulations.

SECTION IX: PREPARATION

THE INFORMATION CONTAINED HEREIN IS GIVEN IN GOOD FAITH,
BUT NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE.

DATE ISSUED: **January 26, 2011**
SUPERSEDES: **March 17, 2008**

BY: Product safety committee
PHONE: 780-440-4923

**Diversity Technologies Corp. is the parent company of
Canamara-United Supply, Hollimex Products, The Drilling Depot and
Westcoast Drilling Supplies.**