

MATERIAL SAFETY DATA SHEET

SECTION I: IDENTIFICATION OF PRODUCT

COMPANY: **Diversity Technologies Corp.** DATE: **July 10, 2009**
8750 – 53rd Ave. PHONE: 780-468-4064
Edmonton, AB T6E 5G2 FAX: 780-469-1899

PRODUCT NAME: **Hydrogel API & Hydrogel 125**

PRODUCT USE: Oilwell drilling fluid additive.
CHEMICAL FAMILY: Natural mineral, Montmorillonite CAS#: 1302-78-9

WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS)

WHMIS CLASSIFICATION: D2A
WORKPLACE HAZARD: Potential carcinogen; contains free silica.

TRANSPORTATION OF DANGEROUS GOODS (TDG)

PROPER SHIPPING NAME: Not regulated under TDG
TDG CLASSIFICATION: Not applicable
UN NUMBER (PIN): Not applicable
PACKING GROUP: Not applicable

SECTION II: HAZARDOUS INGREDIENTS

<u>INGREDIENT</u>	<u>% (w/w)</u>	<u>CAS NUMBER</u>	<u>LD₅₀Oral-Rat</u>	<u>LC₅₀Inhal-Rat</u>	<u>ACGIH-TLV</u>
Silica, crystalline quartz	2 – 6	14808-60-7	Not available	Not available	0.025 mg/m³

SECTION III: HEALTH HAZARDS

ROUTE OF ENTRY: []EYE CONTACT []SKIN [XX]INHALATION []INGESTION
EYE CONTACT: May cause mechanical irritation.
SKIN CONTACT: Possible drying resulting in dermatitis.
INGESTION: No adverse effects expected.
INHALATION: May cause irritation of the upper respiratory tract. This product contains crystalline silica. Breathing silica containing dust may not cause noticeable injury or illness even though permanent lung damage may be occurring. Chronic inhalation may cause silicosis, a progressive, disabling and sometimes fatal lung disease. Chronic inhalation exposure to crystalline silica quartz has been observed to cause lymph node effects, kidney effects and auto-immune disease.

CARCINOGENICITY:	Bentonite is not listed by ACGIH, IARC, NTP or OSHA. Crystalline silica, when inhaled from occupational sources, is considered as a human carcinogen by IARC (Class 1) and by NTP. ACGIH classifies crystalline silica, quartz, as a suspected human carcinogen (A2).
TERATOGENICITY:	No information available.
REPRODUCTIVE TOXICITY:	No information available.
MUTAGENICITY:	Crystalline silica has been shown to cause mutagenic effects in human cells in-vitro.
SYNERGISTIC PRODUCTS:	No information available.

SECTION IV: FIRST AID MEASURES

SKIN CONTACT:	If irritation occurs, or when shift ends, wash with soap and water until clean.
EYE CONTACT:	Flush with gently flowing warm water until irritation ceases. If irritation persists, contact a physician.
INGESTION:	Ingestion of small amounts is not expected to have any harmful effects. If large amounts ingested, get immediate medical attention.
INHALATION:	Move to area free from dust. If symptoms or irritation persist contact a physician. Inhalation may aggravate existing respiratory illness.

SECTION V: PHYSICAL DATA

APPEARANCE AND ODOUR:	Pale grey to buff powder or granules; odourless	
SPECIFIC GRAVITY:	2.5	
BOILING POINT (°C):	Not applicable	
MELTING POINT (°C):	1450	
SOLUBILITY IN WATER:	Insoluble	pH: 8-10 (5% suspension)
PERCENT VOLATILE BY VOLUME:	Not applicable	
EVAPORATION RATE:	Not applicable	
VAPOUR PRESSURE (mmHg):	Not applicable	
VAPOUR DENSITY (air = 1):	Not applicable	
BULK DENSITY:	Not available	

SECTION VI: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT:	Not applicable
FLAMMABLE LIMITS:	Not applicable
EXTINGUISHING MEDIA:	Use media suitable for surrounding fire and packaging.

SPECIAL FIRE FIGHTING
PROCEDURES:
UNUSUAL FIRE AND
EXPLOSION HAZARDS:

Self-contained breathing apparatus required for fire
fighting personnel.
Product becomes very slippery when wet, avoid
using water as fire fighting agent.

SECTION VII: REACTIVITY DATA

STABILITY:	STABLE [XX]	UNSTABLE []
INCOMPATIBILITY (CONDITIONS TO AVOID):	None known.	
CONDITIONS OF REACTIVITY:	Not available.	
HAZARDOUS DECOMPOSITION PRODUCTS:	None known.	
HAZARDOUS POLYMERIZATION:	WILL NOT OCCUR [XX]	MAY OCCUR []

SECTION VIII: PREVENTATIVE MEASURES

SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION:	NIOSH/MESA approved respirators for silica bearing dust.
VENTILATION:	Use local exhaust ventilation, process enclosure or other engineering controls to maintain concentration of airborne dust below TLV.
PROTECTIVE GLOVES:	Generally not necessary; personal preference.
EYE PROTECTION:	Suggest goggles or safety glasses.
OTHER PROTECTIVE EQUIPMENT (Specify):	Ensure emergency eye wash station and safety shower are available.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Avoid creating dust. Avoid breathing dust; wear an approved respirator. Practice reasonable caution and personal cleanliness. Avoid eye contact. Store in cool, dry area. Empty packages contain residual hazardous material; use appropriate safety equipment when handling.

STEPS TO BE TAKEN IN CASE THE MATERIAL IS SPILLED OR RELEASED

Wear an approved respirator. Vacuum if possible to avoid generating airborne dust. Collect uncontaminated material for repackaging. Collect contaminated material in an approved container for disposal. Avoid adding water; the product will become slippery when wet.

WASTE DISPOSAL METHOD

Dispose in accordance with federal, provincial and local regulations. It is the responsibility of the end user to determine if material meets the criteria of hazardous waste at the time of disposal. Empty packaging must be disposed of or recycled in accordance with local regulations.

SECTION IX: PREPARATION

THE INFORMATION CONTAINED HEREIN IS GIVEN IN GOOD FAITH,
BUT NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE.

DATE ISSUED: July 10, 2009

BY: Product safety committee

SUPERSEDES: July 11, 2006

PHONE: 780-440-4923

**Diversity Technologies Corp. is the parent company of
Canamara-United Supply, Hollimex Products, The Drilling Depot and
Westcoast Drilling Supplies.**