

SAFETY DATA SHEET

HIGH CALCIUM QUICKLIME

Section 1. Identification		
GHS product identifier	: HIGH CALCIUM QUICKLIME	
Code	: Not available.	
Other means of identification	: Lime, Quicklime, Calcium Oxide, Burnt Lime, Unslaked Lime, Fluxing Lime.	
Product type	: Solid.	
Relevant identified uses o	f the substance or mixture and uses advised against	
Identified uses	: Neutralization, flocculation, flux(met.), caustic agent, absorption.	
Supplier/Manufacturer	: GRAYMONT #200-10991 Shellbridge Way Richmond, BC V6X 3C6 Canada Phone: 1 604 207-4292 Toll free: 1 866 207-4292 Fax: 1 604 207-9014 Web Site: http://www.graymont.com/	
Emergency telephone number (with hours of operation)	: CANUTEC (613-996-6666) CHEMTREC, US (800-424-9300) INTERNATIONAL: (703-527-3887)	

Section 2. Hazards identification

OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	 SKIN IRRITATION - Category 2 SERIOUS EYE DAMAGE - Category 1 CARCINOGENICITY (inhalation) - Category 1A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (respiratory tract) - Category 1
GHS label elements	
Hazard pictograms	
Signal word	: Danger
Hazard statements	: H318 - Causes serious eye damage. H315 - Causes skin irritation

H315 - Causes skin irritation.

- H350 May cause cancer if inhaled.
- H335 May cause respiratory irritation.
- H372 Causes damage to organs through prolonged or repeated exposure. (respiratory tract)

Precautionary statements

Tel: +1-888-GHS-7769 (447-7769) / +1-450-GHS-7767 (447-7767) www.kmkregservices.com www.askdrluc.com www.ghssmart.com

Section 2. Hazards identification

Descention	DO01 Obtain an aigl instructions hafars use
Prevention	 P201 - Obtain special instructions before use. P202 - Do not bondle until all opfaty processitions have been read and understand
	P202 - Do not handle until all safety precautions have been read and understood. P280 - Wear protective gloves. Wear eye or face protection. Wear protective clothing.
	P200 - Wear protective groves, wear eye of race protection, wear protective clothing. P271 - Use only outdoors or in a well-ventilated area.
	P260 - Do not breathe dust.
	P270 - Do not eat, drink or smoke when using this product.
	P264 - Wash hands thoroughly after handling.
Response	: P314 - Get medical attention if you feel unwell.
	P308 + P313 - IF exposed or concerned: Get medical attention.
	P304 + P340 + P312 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel
	P302 + P352 + P362 + P363 - IF ON SKIN: Wash with plenty of soap and water. Take
	off contaminated clothing. Wash contaminated clothing before reuse. P332 + P313 - If skin irritation occurs: Get medical attention.
	P305 + P351 + P338 + P310 - IF IN EYES: Rinse cautiously with water for several
	minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	Immediately call a POISON CENTER or physician.
Storage	: P401 - Store to minimize dust generation.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: Not applicable.
Other hazards which do not esult in classification/ IHNOC/PHNOC	: None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of identification	: Lime, Quicklime, Calcium Oxide, Burnt Lime, Unslaked Lime, Fluxing Lime.

CAS number/other identifiers

CAS number	: 1305-78-8		
Product code	: Not available.		
Ingredient name		%	CAS number
Calcium oxide Crystalline silica, respirable pow	rder	90 - 100 0.0001 - 1	1305-78-8 14808-60-7

Crystalline silica has been found in some products at or above detection level 0.1%. Concentration is dependent upon limestone source.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.



Section 4. First aid measures

Description of necess	sary first aid measures
Eye contact	: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 20 minutes. Chemical burns must be treated promptly by a physician.
Inhalation	: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. When used under normal conditions quicklime doesn't generate fumes. However dust (Particulates) may be generated. Use dust-mask if dust is present. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Get medical attention immediately. Call a poison center or physician. Flush contaminated skin with plenty of water. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 20 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

<u>Most important symptoms/effects, acute and delayed</u>				
Potential acute health effects				
Eye contact	: Causes serious eye damage.			
Inhalation	: May cause respiratory irritation.			
Skin contact	: Causes skin irritation.			
Ingestion	: No known significant effects or critical hazards.			
Over-exposure signs/sy	<u>mptoms</u>			
Eye contact	: Adverse symptoms may include the following: pain watering redness			
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing burning sensation			
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur			
Ingestion	: Adverse symptoms may include the following: stomach pains			

a.

Section 4. First aid measures

Indication of immediate medical attention and special treatment needed, if necessary		
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. 	
Specific treatments	: No specific treatment.	
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.	

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use dry chemical fire extinguisher.
Unsuitable extinguishing media	: Do not use water or halogenated compounds, except that large amounts of water may be used to deluge small quantities of quicklime.
Specific hazards arising from the chemical	: Not applicable.
Hazardous thermal decomposition products	: None.
Special protective actions for fire-fighters	: First move people out of line-of-sight of the scene and away from windows.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

 Personal precautions, protective equipment and emergency procedures

 For non-emergency
 : No action shall be taken involving any personal risk or without suitable training

 For non-emergency
 : No action shall be taken involving any personal risk or without suitable training

personnel		Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up





Section 6. Accidental release measures

: Move containers from spill area. Do not use water on bulk material spills. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling		
Protective measures	obt bee Use ina cor	t on appropriate personal protective equipment (see Section 8). Avoid exposure - ain special instructions before use. Do not handle until all safety precautions have en read and understood. Do not get in eyes or on skin or clothing. Do not ingest. e only with adequate ventilation. Wear appropriate respirator when ventilation is dequate. Keep in the original container or an approved alternative made from a npatible material, kept tightly closed when not in use. Empty containers retain duct residue and can be hazardous.
Advice on general occupational hygiene	har drir	ting, drinking and smoking should be prohibited in areas where this material is ndled, stored and processed. Workers should wash hands and face before eating, nking and smoking. See also Section 8 for additional information on hygiene asures.
Conditions for safe storage, including any incompatibilities	Sto are mir Co pre	bre in accordance with local regulations. Store in a segregated and approved area. bre in original container protected from direct sunlight in a dry, cool and well-ventilated ta, away from incompatible materials (see Section 10) and food and drink. Store to himize dust generation. Keep container tightly closed and sealed until ready for use. Intainers that have been opened must be carefully resealed and kept upright to event leakage. Do not store in unlabeled containers. Use appropriate containment to bid environmental contamination. Do not store in unlabeled containers.

Section 8. Exposure controls/personal protection

Control parameters

United States

Occupational exposure limits

Ingredient name	Exposure limits
Calcium oxide	ACGIH TLV (United States, 3/2016). TWA: 2 mg/m ³ 8 hours. NIOSH REL (United States, 10/2013). TWA: 2 mg/m ³ 10 hours. OSHA PEL (United States, 6/2016).
Crystalline silica, respirable powder	TWA: 5 mg/m ³ 8 hours. OSHA PEL Z3 (United States, 6/2016). TWA: 250 mppcf 8 hours. Form: Respirable TWA: 10 mg/m ³ 8 hours. Form: Respirable TWA: 5 mg/m3 Form: Respirable fraction TWA: 15 mg/m3 Form: Total dust NIOSH REL (United States, 10/2013). TWA: 0.05 mg/m ³ 10 hours. Form: Respirable dust TWA: 5 mg/m3 Form: Total dust OSHA PEL (United States, 6/2016). TWA: 50 µg/m ³ 8 hours. Form: Respirable dust ACGIH TLV (United States, 3/2016). TWA: 0.025 mg/m ³ 8 hours. Form: Respirable fraction MSHA PEL TWA 8/40 hours: 30 mg/m3/(%SiO2)+2 mg/m3 Form: Total dust 10 mg/m3/(%SiO2)+2 mg/m3 Form: Respirable dust

Spill

Section 8. Exposure controls/personal protection

<u>Canada</u>

Occupational exposure limits

Ingredient name	Exposure limits
Calcium oxide Crystalline silica, respirable powder	 CA Alberta Provincial (Canada, 4/2009). 8 hrs OEL: 2 mg/m³ 8 hours. CA British Columbia Provincial (Canada, 5/2015). TWA: 2 mg/m³ 8 hours. CA Ontario Provincial (Canada, 7/2015). TWA: 2 mg/m³ 8 hours. CA Quebec Provincial (Canada, 1/2014). TWAEV: 2 mg/m³ 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 4 mg/m³ 15 minutes. TWA: 2 mg/m³ 8 hours. CA British Columbia Provincial (Canada, 5/2015). TWA: 0.025 mg/m³ 8 hours. Form: Respirable CA Quebec Provincial (Canada, 1/2014). TWAEV: 0.1 mg/m³ 8 hours. Form: Respirable dust CA Ontario Provincial (Canada, 7/2015). TWA: 0.1 mg/m³ 8 hours. Form: Respirable fraction CA Saskatchewan Provincial (Canada, 7/2013). TWA: 0.05 mg/m³ 8 hours. Form: Respirable fraction CA Saskatchewan Provincial (Canada, 7/2013). TWA: 0.05 mg/m³ 8 hours. Form: Respirable fraction CA Saskatchewan Provincial (Canada, 7/2013). TWA: 0.05 mg/m³ 8 hours. Form: Respirable fraction CA Saskatchewan Provincial (Canada, 4/2009). 8 hrs OEL: 0.025 mg/m³ 8 hours. Form: Respirable particulate.

Appropriate engineering controls	:	Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Engineering controls may be required to control the primary or secondary risks associated with this product.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.
Individual protection measur	res	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/ or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.



Section 8. Exposure controls/personal protection

Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Wear an appropriate NIOSH approved respirator if concentration levels exceed the safe exposure limits.

Section 9. Physical and chemical properties

Appearance	
Physical state	: Solid. [Crystalline.]
Color	: White.
Odor	: Odorless + soil like smell.
Odor threshold	: Not available.
рН	: 12.45 [Sat. soln.] at 25°C
Melting point	: 2570 to 2625°C (4658 to 4757°F)
Boiling point	: 2850°C (5162°F)
Flash point	: Not applicable.
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Not available.
Vapor pressure	: Not available.
Vapor density	Not available.
Relative density	: 3.25 to 3.28
Solubility	: Not available.
Solubility in water	: 0.125 g/100 g at 20°C
Partition coefficient: n- octanol/water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Not available.

Section 10. Stability and reactivity

Reactivity	: Reacts violently with strong acids. Reacts with water to form Calcium Hydroxide. The heat generated when mixed with water or moist air is sufficient enough to ignite surrounding materials such as paper, wood or cloth.	
Chemical stability	: The product is stable.	
Possibility of hazardous reactions	: Exothermic reaction to water.	
Conditions to avoid	: Do not allow quicklime to come into contact with incompatible materials. e.g. Water, acids, reactive fluoridated compounds, reactive brominated compounds. reactive powdered metals, organic acid anhydrides, nitro-organic compounds, reactive phosphorous compounds, interhalogenated compounds.	
KMK Regulatory Services	Tel: +1-888-GHS-7769 (447-7769) / +1-450-GHS-7767 (447-7767) 7 www.kmkregservices.com www.askdrluc.com www.ghssmart.com 7	7/13



Section 10. Stability and reactivity

Incompatible materials

: Reactive or incompatible with the following materials: oxidizing materials, acids and moisture.

Hazardous decomposition : None.

products

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

There is no data available.

Irritation/Corrosion

There is no data available.

Sensitization

There is no data available.

Mutagenicity

There is no data available.

Carcinogenicity

Classification

Product/ingredient name	OSHA	IARC	NTP	ACGIH	EPA	NIOSH
Crystalline silica, respirable powder	-	1	Known to be a human carcinogen.	A2	-	+

Reproductive toxicity

There is no data available.

Teratogenicity

There is no data available.

Specific target organ toxicity (single exposure)

Name		Route of exposure	Target organs
Calcium oxide	Category 3	Not applicable.	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
Crystalline silica, respirable powder	Category 1	Inhalation	respiratory tract

Aspiration hazard

There is no data available.

Information on the likely routes of exposure

: Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects

	teritiar acate ricultin encots		
E	ye contact	:	Causes serious eye damage.
In	halation	:	May cause respiratory irritation.
S	kin contact	:	Causes skin irritation.
In	gestion	÷	No known significant effects or critical hazards.

Tel: +1-888-GHS-7769 (447-7769) / +1-450-GHS-7767 (447-7767) www.kmkregservices.com www.askdrluc.com www.ghssmart.com

Section 11. Toxicological information

	-
Symptoms related to the phy	<u>/sical, chemical and toxicological characteristics</u>
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing burning sensation
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur
Ingestion	: Adverse symptoms may include the following: stomach pains
Delayed and immediate effect	cts and also chronic effects from short and long term exposure
Short term exposure	
Potential immediate effects	: No known significant effects or critical hazards.
Potential delayed effects	: No known significant effects or critical hazards.
Long term exposure	
Potential immediate effects	: No known significant effects or critical hazards.
Potential delayed effects	: No known significant effects or critical hazards.
Potential chronic health eff	<u>ects</u>
General	: Causes damage to organs through prolonged or repeated exposure.
Carcinogenicity	: May cause cancer if inhaled. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

There is no data available.

Section 12. Ecological information

<u>Toxicity</u>			
Product/ingredient name	Result	Species	Exposure
Calcium oxide	Chronic NOEC 100 mg/L Fresh water	Fish - Oreochromis niloticus - Juvenile (Fledgling, Hatchling, Weanling)	46 days

Persistence and degradability

There is no data available.

Bioaccumulative potential



HIGH CALCIUM QUICKLIME

Section 12. Ecological information

Product/ingredient name	LogPow	BCF	Potential
Calcium oxide	-	2.34	low

Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT	TDG	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.	UN1910
UN proper shipping name	-	-	-	CALCIUM OXIDE
Transport hazard class(es)	-	-	-	8
Packing group	-	-	-	111
Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

AERG : Not applicable.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.





Section 15. Regulatory information

0							
U.S. Federal regulations	:	United States inventor reporting (IUR).	ory (TSC	A 8b) : Calcium	n Oxide is subj	ject to invento	ry update
		RCRA classification:	Calcium	Oxide is not lis	sted or classifi	ed.	
		CWA-311 : Calcium O hazardous substances				an Water Act	(CWA) list of
		CERCLA: Calcium Ox	ide is no	t listed.			
		FDA : Calcium Oxide h by FDA. See 21CFR1 affirmed as generally	84.1210.	(CFR Title 21			
Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	:	Not listed					
Clean Air Act Section 602 Class I Substances	:	Not listed					
Clean Air Act Section 602 Class II Substances	:	Not listed					
DEA List I Chemicals (Precursor Chemicals)	:	Not listed					
DEA List II Chemicals (Essential Chemicals)	:	Not listed					
SARA 302/304							
Composition/information	on	ingredients					
No products were found.							
SARA 304 RQ	:	Not applicable.					
<u>SARA 311/312</u>							
Classification	:	Immediate (acute) hea Delayed (chronic) hea					
Composition/information	on	ingredients					
Name			Fire hazard	Sudden release of	Reactive	Immediate (acute) bealth	Delayed (chronic)

	release of pressure		health	(chronic) health hazard
No. No.		No. No.	Yes. No.	No. Yes.

SARA 313

	Product name	CAS number
Form R - Reporting requirements	Not listed	-
Supplier notification	Not listed	-

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts	: The following components are listed: Calcium oxide; Crystalline silica, respirable powder
New York	: None of the components are listed.
New Jersey	: The following components are listed: Calcium oxide; Crystalline silica, respirable powder
Pennsylvania	: The following components are listed: Calcium oxide; Crystalline silica, respirable powder

Section 15. Regulatory information

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

Ingredient name	Cancer	Reproductive		Maximum acceptable dosage level
Crystalline silica, respirable powder	Yes.	No.	No.	No.

Canada

Canadian lists

Canadian NPRI

- : None of the components are listed.
- CEPA Toxic substances Canada inventory
- : None of the components are listed.

: All components are listed or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health : 3 * Flammability : 0 Physical hazards :

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

1

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)

Health: 3 Flammability: 0 Instability: 1

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Procedure used to derive the classification

Classification	Justification
SKIN IRRITATION - Category 2	Expert judgment
SERIOUS EYE DAMAGE - Category 1	On basis of test data
CARCINOGENICITY (inhalation) - Category 1A	Expert judgment
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (respiratory tract) - Category 1	Calculation method

History

Date of issue mm/dd/yyyy	: 01/30/2017
Date of previous issue	: 06/15/2015
Version	: 2
Prepared by	: KMK Regulatory Services Inc.





Section 16. Other information

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

