

SECTION 1: IDENTIFICATION

PRODUCT IDENTIFIER: REV DUST

OTHER MEANS OF IDENTIFICATION: Smectite

RECOMMENDED USE: Oilwell drilling fluid additive

RESTRICTIONS ON USE:

SUPPLIER IDENTIFIER:

Di-Corp

8750-53 Ave

Edmonton, AB T6E 5G2

780-440-4923

EMERGENCY PHONE NUMBER: 780-468-4064 (24 hr)

SECTION 2: HAZARD IDENTIFICATION

CLASSIFICATION: Carcinogenicity – Category 1A

STOT - RE - Category 1

LABEL SYMBOL:

SIGNAL WORD: DANGER

CLASSIFICATION INFORMATION: May cause cancer by inhalation.

Causes damage to lungs through prolonged or repeated inhalation.

PRECAUTIONARY STATEMENTS: Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust.

Wash hands, face and any exposed skin thoroughly after handling.

Do not eat, drink or smoke when using this product.

In case of inadequate ventilation wear respiratory protection.

IF exposed or concerned: Get medical advice.

Dispose of contents and/or container in accordance with local regulations, regional,

national, and/or international regulations.

OTHER HAZARDS: Not available.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

 CHEMICAL NAME
 CAS NUMBER
 CONCENTRATION

 Smectite
 1302-78-9
 >95% (w/w)

 Quartz; crystalline silica
 14808-60-7
 <1 - 5% (w/w)</td>

SECTION 4: FIRST AID MEASURES

SKIN CONTACT: If irritation occurs, before breaks and when shift ends wash with soap and water. If

irritation develops and persists seek medical attention.

© Di-Corp 2018 Page 1 of 5



EYE CONTACT: Flush with gently flowing warm water until particles are removed and irritation ceases.

If irritation persists seek medical attention.

INGESTION: No first aid required for ingestion of small quantities. If large amount is ingested

obtain medical attention.

INHALATION: Move to area free from dust. If breathing difficulties continue, obtain medical

attention. Inhalation may aggravate existing respiratory illness.

MOST IMPORTANT SYMPTOMS / EFFECTS: No known acute health effects. Long-term inhalation of crystalline silica can cause

silicosis, lymph node effects, kidney effects, auto-immune disease and cancer.

IMMEDIATE MEDICAL ATTENTION /

SPECIAL TREATMENT:

Treat symptomatically.

SECTION 5: FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Use media suitable for packaging and surrounding fire.

UNSUITABLE EXTINGUISHING MEDIA: None.

SPECIFIC FIRE HAZARDS: None. Will not burn. HAZARDOUS COMBUSTION PRODUCTS: Not applicable.

SPECIAL PROTECTIVE EQUIPMENT & Self-contained breathing apparatus required for fire-fighting personnel.

PRECAUTIONS:

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIMENT AND EMERGENCY PROCEDURES

Use appropriate safety equipment. Avoid creating dust clouds. Avoid breathing dust; wear an approved respirator. Remove and thoroughly clean contaminated clothing before rewearing.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEAN UP

Vacuum up, if possible, to avoid generating airborne dust. Collect uncontaminated material for repackaging. Collect contaminated material in approved containers for disposal. Do not flush with water; becomes slippery when wet.

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING

Avoid creating dust. Avoid breathing dust; wear an approved respirator. Practice reasonable caution and personal cleanliness. Launder contaminated clothing before reuse. Slippery when wet. Empty packages contain residual hazardous material and should be handled as if full.

CONDITIONS FOR SAFE STORAGE & INCOMPATIBILITIES

Store in cool, dry area.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

COMPONENTEXPOSURE LIMITSSmectiteACGIH TLV = 10 mg/m^3

Quartz; crystalline silica ACGIH TWA = 0.025 mg/m³ (respirable)

© Di-Corp 2018 Page 2 of 5



Page 3 of 5

ENGINEERING CONTROLS: Maintain adequate engineering controls and/or ventilation to keep hazardous

ingredient(s) below statutory limits.

PERSONAL PROTECTIVE MEASURES

RESPIRATORY PROTECTION: NIOSH approved dust masks or respirators for silica bearing dust.

PROTECTIVE GLOVES: Personal preference.

EYE PROTECTION: Safety glasses with side shields recommended.

OTHER PROTECTIVE EQUIPMENT (SPECIFY): Ensure eyewash station and emergency shower are available.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Gray powder

ODOUR: Earthy odour

ODOUR THRESHOLD: Not applicable

pH: 7 - 10

MELTING POINT / FREEZING POINT: Not applicable **BOILING POINT / RANGE:** Not applicable FLASH POINT: Not applicable **EVAPORATION RATE:** Not applicable FLAMMABILITY: Not flammable FLAMMABILITY / EXPLOSIVE LIMITS: Not applicable **VAPOUR PRESSURE:** Not applicable VAPOUR DENSITY: Not applicable RELATIVE DENSITY: 2.5 - 2.7

SOLUBILITY: Insoluble in water
PARTION COEFFICIENT: Not available
AUTO-IGNITION TEMPERATURE: Not applicable
DECOMPOSITION TEMPERATURE: Not available
VISCOSITY: Not available

SECTION 10: STABILITY AND REACTIVITY

REACTIVITY: Not reactive under normal conditions of storage or use.

CHEMICAL STABILITY: Stable.

© Di-Corp 2018

POSSIBILITY OF HAZARDOUS REACTIONS: None known.
CONDITIONS TO AVOID: None known.
INCOMPATIBLE MATERIALS: None known.
HAZARDOUS DECOMPOSITION PRODUCTS: Not available.

SECTION 11: TOXICOLOGICAL INFORMATION

PRODUCT TOXICITY: No product or component information available.

SKIN CONTACT:

Possible drying resulting in dermatitis.

EYE CONTACT:

May cause mechanical irritation.

Low oral toxicity. No effects expected.



INHALATION: May cause irritation of the upper respiratory tract. This product contains crystalline

silica. Breathing silica containing dust may not cause noticeable injury or illness even though permanent lung damage may be occurring. Chronic inhalation may cause silicosis, a progressive, disabling and sometimes fatal lung disease. Chronic inhalation exposure to crystalline silica quartz has been observed to cause lymph node effects,

kidney effects and auto-immune disease.

CARCINOGENICITY: Smectite is not listed by ACGIH, IARC, NTP or OSHA. Crystalline silica, when inhaled

from occupational sources, is considered as a human carcinogen by IARC (Class 1) and by NTP. ACGIH classifies crystalline silica, quartz, as a suspected human carcinogen

(A2).

TERATOGENICITY: No information available.

REPRODUCTIVE TOXICITY: No information available.

MUTAGENICITY: Crystalline silica has been shown to cause mutagenic effects in human cells in-vitro.

CHRONIC TOXICITY: Prolonged inhalation of respirable crystalline silica may cause lung disease, silicosis,

lung cancer and other effects.

TARGET ORGAN EFFECTS: Respiratory system (lungs).

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICITY: No data available.

PERSISTENCE AND DEGRADABILITY: Not applicable to inorganic substances.

BIOACCUMULATIVE POTENTIAL:

MOBILITY IN SOIL:

No data available.

OTHER ADVERSE EFFECTS:

No data available.

SECTION 13: DISPOSAL CONSIDERATIONS

Dispose of in accordance with federal, provincial and local regulations. It is the responsibility of the end-user to determine if material meets the criteria of hazardous waste at the time of disposal. May be disposed of as an inert solid in a sanitary landfill in some locations: Check with local operator. Empty packages should be taken for local recycling, recover or waste disposal: Check with local waste operator.

SECTION 14: TRANSPORTATION INFORMATION

TDG: Not regulated DOT: Not regulated IATA: Not regulated IMDG: Not regulated UN NUMBER: Not applicable PROPER SHIPPING NAME: Not applicable CLASS: Not applicable PACKING GROUP: Not applicable IMDG HAZARDS: Not applicable **BULK TRANSPORT:** Not applicable SPECIAL PRECAUTIONS: Not applicable

© Di-Corp 2018 Page 4 of 5



SECTION 15: REGULATORY INFORMATION

DSL: All ingredients are on, or are exempt from, the DSL.

WHMIS CLASS: D2A

TSCA: All components are listed on the inventory or are exempt.

SECTION 16: OTHER INFORMATION

REVISION DATE: November 30, 2018

The information contained herein is given in good faith, but no warranty, expressed or implied, is made.

© Di-Corp 2018 Page 5 of 5