

SAFETY DATA SHEET SODA ASH

SECTION 1: IDENTIFICATION

PRODUCT IDENTIFIER: SODA ASH

OTHER MEANS OF IDENTIFICATION: Sodium carbonate

RECOMMENDED USE: Oilwell drilling fluid and cement additive

RESTRICTIONS ON USE:

SUPPLIER IDENTIFIER:

None known

Di-Corp

Edmonton, AB T6E 5G2

780-440-4923

8750-53 Ave

EMERGENCY PHONE NUMBER: 780-468-4064 (24 hr)

SECTION 2: HAZARD IDENTIFICATION

CLASSIFICATION: Serious eye damage / eye irritation – Category 2

LABEL SYMBOLS:

 $\langle ! \rangle$

SIGNAL WORD: WARNING

CLASSIFICATION INFORMATION: Causes serious eye irritation.

Wash face, hands and any exposed skin thoroughly after handling. Wear eye protection/ face

protection.

PRECAUTIONARY STATEMENTS:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

OTHER HAZARDS: None known.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL NAME CAS NUMBER CONCENTRATION

Sodium carbonate 497-19-8 100

SECTION 4: FIRST AID MEASURES

SKIN CONTACT: Wash thoroughly with water and soap. If irritation occurs and persists, obtain medical

attention. Remove and launder contaminated clothing before rewearing.

EYE CONTACT: Immediately flush with gently flowing warm water for minimum 15 minutes. Hold eyelids

open to ensure thorough flushing. Neutral saline may be used as soon as it is available.

Obtain medical attention when flushing is complete and no further irritation is felt.

INGESTION: Do not induce vomiting. Rinse mouth with water. Give one to two glasses of water dilute.

Obtain medical attention immediately. Never give anything by mouth if victim is

unconscious, rapidly losing consciousness or convulsing.

INHALATION: Move to area free from dust. If victim is not breathing, if breathing is irregular or if

respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. If

breathing difficulties or distress continues obtain medical attention.

MOST IMPORTANT SYMPTOMS / EFFECTS:

IMMEDIATE MEDICAL ATTENTION / Treat symptomatically.

SPECIAL TREATMENT:

Causes serious eye damage / eye irritation.

© Di-Corp 2018 Page 1 of 4



SAFETY DATA SHEET SODA ASH

SECTION 5: FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Use media appropriate for packaging and surrounding materials.

UNSUITABLE EXTINGUISHING MEDIA: None

SPECIFIC FIRE HAZARDS: Noncombustible. Soda ash does not burn but may decompose upon heating to produce

corrosive and/or toxic fumes.

HAZARDOUS COMBUSTION PRODUCTS: Toxic sodium oxide fumes can be generated by thermal decomposition at elevated

temperatures. Oxides of carbon.

SPECIAL PROTECTIVE EQUIPMENT &

PRECAUTIONS:

Self-contained breathing apparatus required for fire-fighting personnel.

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIMENT AND EMERGENCY PROCEDURES

Wear appropriate safety gear including eye and respiratory protection.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEAN UP

Collect dry material by sweeping and shoveling; liquid material can be removed with a vacuum truck. Collect uncontaminated material for repackaging. Collect contaminated material in an approved container for disposal. Flush spill area thoroughly with water.

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING

Avoid contact with eyes or prolonged skin contact. Avoid breathing dust. Use good personal hygiene and housekeeping. Launder contaminated clothing before reuse.

CONDITIONS FOR SAFE STORAGE & INCOMPATIBILITIES

Store in a cool, dry, well-ventilated place away from acids. Product is hygroscopic, prolonged storage may cause product to cake and become wet from atmospheric moisture. Obey hazard warnings and handle empty containers as if they were full.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE LIMITS: Not established. Local nuisance dust levels apply.

ENGINEERING CONTROLS: Use only with adequate ventilation. If user operations generate dust use process enclosure,

local exhaust ventilation or other engineering controls to keep worker exposure below limits.

PERSONAL PROTECTIVE MEASURES

RESPIRATORY PROTECTION: Approved dust masks required for dust levels below TLV. Use a properly fitted particulate

filter respirator complying with an approved standard if airborne concentrations exceeds TLV

or if a risk assessment indicates this is necessary.

PROTECTIVE GLOVES: Rubber gauntlets recommended.

EYE PROTECTION: Wear tight fitting chemical goggles. Do not wear contact lenses.

OTHER PROTECTIVE EQUIPMENT (SPECIFY): Protective clothing as required to prevent contact. Ensure eye-wash station and emergency

shower are available.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: White granules

ODOUR: Odourless

ODOUR THRESHOLD: Not applicable

pH: 11.4 (1% aqueous solution)

MELTING POINT / FREEZING POINT: 153°C

BOILING POINT / RANGE: Not available

FLASH POINT: Not applicable

© Di-Corp 2018 Page 2 of 4



SAFETY DATA SHEET SODA ASH

EVAPORATION RATE:

FLAMMABILITY:

FLAMMABILITY / EXPLOSIVE LIMITS:

VAPOUR PRESSURE:

VAPOUR DENSITY:

Not applicable

Not applicable

RELATIVE DENSITY: 2.52

SOLUBILITY: 212.5 g/L H_2O @ 20°C

PARTION COEFFICIENT: Not available
AUTO-IGNITION TEMPERATURE: Not applicable

DECOMPOSITION TEMPERATURE: 400°C

VISCOSITY: Not available

SECTION 10: STABILITY AND REACTIVITY

REACTIVITY: Contact with acids will release carbon dioxide gas. Can react violently with red, hot

aluminum metal; fluorine gas; lithium; and 2,4,6-trinitrotoluene. Sodium carbonate solutions (concentrations up to 35%) are corrosive to aluminum, lead, and zinc and zinc brasses at 21°C. Solid sodium carbonate is corrosive to aluminum at 100% relative humidity and normal

temperatures.

CHEMICAL STABILITY: Stable.

POSSIBILITY OF HAZARDOUS REACTIONS: None under normal conditions of use.

CONDITIONS TO AVOID: Exposure to air or moisture over prolonged periods.

INCOMPATIBLE MATERIALS: Aluminum. Powdered aluminum. Acids.

HAZARDOUS DECOMPOSITION PRODUCTS: Sodium oxides. Carbon oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

PRODUCT TOXICITY: LD50 (Oral, rat) = 2800 mg/kg

LD50 (Dermal, rabbit) > 2000 mg/kg LC50 (Inhal, rat) = 2.3 mg/L/2hr

SKIN CONTACT: Non-irritating to intact skin. Minor irritation may occur on abraded skin. Prolonged contact

may cause irritation (red, dry, cracked skin).

EYE CONTACT: Dust and concentrated solutions may cause moderate to severe eye irritation.

INGESTION: Although low in toxicity, ingestion can be harmful. May cause nausea, vomiting,

stomachache and diarrhea.

INHALATION: Excessive levels of airborne dust may irritate the mucous membranes and upper respiratory

tract.

CARCINOGENICITY: Not listed by NTP, IARC, OSHA or ACGIH.

TERATOGENICITY: No information available.

REPRODUCTIVE TOXICITY: No information available.

MUTAGENICITY: No information available.

CHRONIC TOXICITY: No information available.

TARGET ORGAN EFFECTS: Not available.

© Di-Corp 2018 Page 3 of 4



SAFETY DATA SHEET SODA ASH

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICITY: LC50 (bluegill sunfish) = 300 mg/L/96hr

EC50 (ceriodaphnia) = 200 - 227 mg/L/48hr

PERSISTENCE AND DEGRADABILITY: Not applicable to inorganic substances.

BIOACCUMULATIVE POTENTIAL: Does not bioaccumulate.

MOBILITY IN SOIL: Dissociates into ions.

OTHER ADVERSE EFFECTS: None know.

SECTION 13: DISPOSAL CONSIDERATIONS

Dispose of in accordance with federal, provincial and local regulations. It is the responsibility of the end-user to determine if material meets the criteria of hazardous waste at the time of disposal. Empty containers, which have not been cleaned and purged, contain residual hazardous material and must be recycled, or disposed of, in accordance with local regulations.

SECTION 14: TRANSPORTATION INFORMATION

TDG Not regulated DOT Not regulated IATA Not regulated **IMDG** Not regulated UN NUMBER: Not applicable PROPER SHIPPING NAME: Not applicable CLASS: Not applicable PACKING GROUP: Not applicable

IMDG HAZARDS: Not a marine pollutant

BULK TRANSPORT: Not regulated

SPECIAL PRECAUTIONS: None

SECTION 15: REGULATORY INFORMATION

DSL: Listed WHMIS CLASS: D2B, E TSCA: Listed

SECTION 16: OTHER INFORMATION

REVISION DATE: November 7, 2019
REPLACES: February 14, 2018

The information contained herein is given in good faith, but no warranty, expressed or implied, is made.

© Di-Corp 2018 Page 4 of 4