

Section 01 Identification

Product Identifier Sodium Hypochlorite 12-16%

Sodium Hypochlorite 12%, NSF® - 60

Sodium Hypochlorite 12.5% With 1% Alkalinity

Sodium Hypochlorite 13%, NSF® - 60 Sodium Hypochlorite 15%, NSF® - 60 Sodium Hypochlorite 16%, NSF® - 60

Other Means of Identification Sodium hypochlorite, Bleach, Chlorox, Hypochlorous acid, sodium salt, Javel water, liquid

bleach.

Product Use and Restrictions

on Use

Bleaching agent, source of available chlorine, deodorizer.

Initial Supplier Identifier ClearTech Industries Inc

1500 Quebec Avenue Saskatoon, SK. Canada

S7K 1V7

Phone: 800.387.7503 Fax: 888.281.8109 www.cleartech.ca

Prepared By ClearTech Industries Inc. technical writer

24-Hour Emergency Phone 306.664.2522

Section 02 Hazard Identification

Physical Hazards

Corrosive to metals Category 1

Health Hazards

Skin corrosion / irritation Category 1B
Serious eye damage / eye Category 1

irritation

Signal Word

Danger

Hazard Statements

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

Pictograms



Customer Service: 800.387.7503 www.cleartech.ca Emergency: 306.664.2522

Revision Date: June 11, 2020

Page 1 of 9

Precautionary Statements

Prevention

P234 Keep only in original packaging.

P260 Do not breathe vapours, fumes, and mists.

P264 Wash affected body parts thoroughly after handling.

P280 Wear protective gloves, protective clothing, eye protection, face protection

Response

P301 P330 P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 P361 P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or

P363 shower. Wash contaminated clothing before reuse.

P304 P340 P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a

POISON CENTER or doctor.

P305 P351 P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P390 Absorb spillage to prevent material damage.

Storage

P405 Store locked up.

Disposal

P501 Dispose of contents / container in accordance with all federal, provincial and / or local regulations including the Canadian Environmental Protection Act.

Hazards Not Otherwise Classified

Contact with acids liberates toxic gas.

Supplemental Information

Not available

Section 03 Composition / Information on Ingredients

Hazardous Ingredients:

Chemical name Common name(s) **CAS** number Concentration (w/w%)

Hypochlorous acid, sodium salt Sodium hypochlorite 7681-52-9 10-16%

Section 04 First-Aid Measures

Description of necessary first-aid measures

Customer Service: 800.387.7503

Remove source of exposure or move person to fresh air and keep comfortable for breathing. Call a POISON

CENTER or doctor. If breathing has stopped, trained personnel should begin rescue breathing or if the heart has stopped, immediately start cardiopulmonary resuscitation (CPR) or automated external defibrillation

(AED). Avoid mouth to mouth contact by using a barrier device. May release toxic chlorine gas.

Ingestion Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor. If vomiting occurs

naturally, lie on your side, in the recovery position.

Skin Avoid direct contact. Wear chemical protective clothing, if necessary. Take off immediately contaminated contact clothing, shoes and leather goods. Rinse skin with lukewarm, gently flowing water / shower for 30 minutes. Immediately call a POISON CENTER or doctor. Wash contaminated clothing before re-use, or discard.

www.cleartech.ca Emergency: 306.664.2522 Revision Date: June 11, 2020 Page 2 of 9

Eye contact Avoid direct contact. Wear chemical protective gloves, if necessary. Remove source of exposure or move person to fresh air. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for 30 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. Immediately call a POISON CENTER or doctor.

Most important symptoms and effects, both acute and delayed

Inhalation Causes severe burns to the mouth and throat (mist). May release toxic and irritating chlorine gas.

Ingestion Causes burns to the mouth and throat.

Skin contact Causes severe skin burns. Eye contact Causes serious eye damage.

Further information For further information see Section 11 Toxicological Information.

Section 05 Fire Fighting Measures

Suitable extinguishing media Extinguish fire using extinguishing agents suitable for the surrounding fire.

Unsuitable extinguishing media

Do NOT use dry chemical fire extinguishing agents containing ammonium compounds (such as some A:B:C agents), since an explosive compound can be formed. Water jets are

not recommended in fires involving chemicals.

Specific hazards arising from

the chemical

Explosive decomposition may occur under fire conditions and closed containers may rupture violently due to a rapid decomposition, if exposed to fire or excessive heat for a sufficient period of time.

Special protective equipment

for fire-fighters

Wear NIOSH-approved self-contained breathing apparatus and chemical-protective

clothing.

Section 06 Accidental Release Measures

Personal Precautions / Protective Equipment / **Emergency Procedures** Wear appropriate personal protective equipment (See Section 08 Exposure Controls and Personal Protection). Stay upwind, ventilate area. Do not breathe vapours, fumes, and mists. Do not use material handling equipment with exposed metal surfaces. Sodium hypochlorite solutions release chlorine when in contact with acids or oxidizable materials. such as oganic material or most metals. Chlorine is a respiratory irritant, so respiratory protection is advised.

Environmental Precautions

Prevent material from entering waterways, sewers or confined spaces. Notify local health and wildlife officials. Notify operators of nearby water intakes.

Methods and Materials for Containment and Cleaning Up

SMALL SPILLS: Stop or reduce leak if safe to do so. Clean up spill with non-reactive absorbent and place in suitable, covered, labeled containers. Flush area with water. Contaminated absorbent material may pose the same hazards as the spilled product. Use vented containers to avoid pressure buildup.

LARGE SPILLS: Contact fire and emergency services and supplier for advice.

Section 07 Handling and Storage

Precautions for Safe Handling Use proper equipment for lifting and transporting all containers. Use sensible industrial hygiene and housekeeping practices. Wash thoroughly after handling. Avoid all situations that could lead to harmful exposure. Prevent the release of vapours, fumes, and mists into the workplace air.

> Inspect containers for damage or leaks before handling. If the original label is damaged or missing replace with a workplace label. Have suitable emergency equipment for fires, spills and leaks readily available.

Never return contaminated material to its original container.

Customer Service: 800.387.7503 www.cleartech.ca Emergency: 306.664.2522 Revision Date: June 11, 2020 Page 3 of 9

Conditions for Safe Storage

Store in a cool, dry, well-ventilated area, out of direct sunlight, away from heat sources and incompatible materials. Always store in original labeled container. Keep containers tightly closed when not in use and when empty. Empty containers may contain hazardous residues. Protect label and keep it visible. Do not transfer to metal containers. Strong solutions (greater than 10% available chlorine) may slowly give off chlorine during storage, especially when warm (above 18°C). Vent caps are required to prevent a build-up of pressure that could cause containers to burst.

Incompatibilities

Acids, such as sulphuric, nitric, hydrochloric, phosphoric, flurosilicic (HFSA), sulphonic,

acetic, citric, oxalic, and formic.

Oxidizing agents, such as oxygen, hydrogen peroxide, sulphuric and nitric acids and

permanganates.

Reducing agents, such as hydrogen, sodium borohydride, sulphur dioxide, thiosulphates,

hydrazine, phosphites, carbon, and oxalic, formic and ascorbic acid.

Organic material, such as wood, paper, gasoline, diesel, solvents and some glycol based

heat transfer fluids

Metals, such as aluminum, steel, and brass.

Section 08 Exposure Controls and Personal Protection

Exposure limits

Component	Regulation	Type of listing	Value
Sodium Hypochlorite	NIOSH	REL	2 mg/m³
	OSHA	PEL	2 mg/m³
Chlorine	ACGIH	TWA	0.1 ppm

Engineering controls

Ventilation Requirements

Mechanical ventilation (dilution or local exhaust), process or personnel enclosure and control of process conditions should be provided in accordance with all fire codes and regulatory requirements. Supply sufficient replacement air to make up for air removed by exhaust systems.

Other

An emergency shower and eyewash station should be available, tested, and be in close proximity to the product being handled in accordance with provincial regulations.

Protective equipment

The following are recommendations only. It is the responsibility of the employer / user to conduct a hazard assessment of the process in which this product being used and determine the proper engineering controls and PPE for their process. Additional regulatory and safety information should be sought from local authorities and, if needed, a professional industrial hygienist.

Eye and face protection

Where there is potential eye or face exposure, tightly fitting safety goggles and a face shield or a full face respirator or similar protective equipment which protects the wearer's face and eyes are recommended. Contact lenses are not recommended; they may contribute to severe eye injury.

Hand and body protection

Disposable latex or nitrile gloves are recommended to prevent incidental contact. Butyl rubber, neoprene, or PVC skin protection is recommended for extended contact. Leather gloves are not recommended for chemical protection. Refer to manufacturer's specifications for breakthrough times and permeability information; note that breakthrough times and permeability vary with temperature, application and age of material. Continued use of contaminated safety gear or clothing is not recommended; wash before reuse or discard.

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment.

Customer Service: 800.387.7503 www.cleartech.ca Emergency: 306.664.2522 Revision Date: June 11, 2020

NIOSH respirator recommendations for: Chlorine

Up to: 5 ppm

(APF = 10) Any chemical cartridge respirator with cartridge(s) providing protection against Chlorine

(APF = 10) Any supplied-air respirator

Up to: 10 ppm

(APF = 25) Any supplied-air respirator operated in a continuous-flow mode

(APF = 25) Any powered, air-purifying respirator with cartridge(s) providing protection against Chlorine

(APF = 50) Any chemical cartridge respirator with a full facepiece and cartridge(s) providing protection against Chlorine

(APF = 50) Any air-purifying, full-facepiece respirator (gas mask) with a chin-style, front- or back-mounted canister providing protection against Chlorine

(APF = 50) Any self-contained breathing apparatus with a full facepiece.

(APF = 50) Any supplied-air respirator with a full facepiece

Emergency or planned entry into unknown concentrations or IDLH conditions:

(APF = 10,000) Any self-contained breathing apparatus that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode

(APF = 10,000) Any supplied-air respirator that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode in combination with an auxiliary self-contained positive-pressure breathing apparatus

Escape:

(APF = 50) Any air-purifying, full-facepiece respirator (gas mask) with a chin-style, front- or back-mounted canister providing protection against Chlorine

Any appropriate escape-type, self-contained breathing apparatus

Thermal hazards Not available

Section 09 Physical and Chemical Properties

Appearance

Physical state Liquid

Colour Clear, greenish-yellow solution

Odour Strong chlorine odour

Odour threshold Not available

Property

pH 10.8-11.2

Melting point / freezing point Not available

Initial boiling point and Not available

boiling range

Revision Date: June 11, 2020

Flash point

Evaporation rate

Flammability

Upper flammable limit

Lower flammable limit

Not available

Not available

Not available

Customer Service: 800.387.7503 <u>www.cleartech.ca</u> Emergency: 306.664.2522

Vapour pressureNegligibleVapour densityNot availableRelative densityNot applicable

Solubility Completely soluble in water

Partition coefficient: n-

octanol/water

Log POW = ~-3.42

Auto-ignition temperature Not available

Decomposition temperature Sodium hypochlorite's decomposition rate is an exponential function of temperature. Each

increase of 10 °C will increase the degredation rate by a factor of 2 to 4 (there is

disagreement in the literature).

Viscosity
Not available
Specific gravity
1.1-1.2 g/mL
Formula
NaOCI
Molecular weight
74.44 g/mol

Section 10 Stability and Reactivity

Reactivity May be corrosive to metals. Reacts violently with acids.

Stability Sodium hypochlorite solutions are unstable and will decompose over time. Sodium

hypochlorite's decomposition rate is an exponential function of temperature. Each increase of 10 °C will increase the degredation rate by a factor of 2 to 4 (there is disagreement in the literature). Exposure to ultraviolet light (sunlight) will accelerate the degredation of sodium

hypochlorite.

Possibility of hazardous

reactions

Hazardous polymerization is not known to occur. Reacts with acids to form hypochlorous

acid, a powerful oxidizing agent, which degrades into toxic chlorine gas.

Conditions to avoid Avoid contact with incompatible materials. Do not heat. Do not freeze.

Incompatible materials Acids, such as sulphuric, nitric, hydrochloric, phosphoric, flurosilicic (HFSA), sulphonic,

acetic, citric, oxalic, and formic.

Oxidizing agents, such as oxygen, hydrogen peroxide, sulphuric and nitric acids and

permanganates.

Reducing agents, such as hydrogen, sodium borohydride, sulphur dioxide, thiosulphates,

hydrazine, phosphites, carbon, and oxalic, formic and ascorbic acid.

Organic material, such as wood, paper, gasoline, diesel, solvents and some glycol based

heat transfer fluids

Metals, such as aluminum, steel, and brass.

Hazardous decomposition

products

Chlorine, sodium chlorate.

Section 11 Toxicological Information

Acute Toxicity (LD50 / LC50 values)

Component	Route	Species	Value	Exposure time
Sodium Hypochlorite	Oral	Rat	>5,000 mg/kg bw	

Chlorine Inhalation Mouse 137 ppm 1 hour

Toxic Health Effect Summary

Chemical Toxicity caused primarily by high pH and oxidative potential. Hypochlorites may react with organic characteristics molecules to form organochlorides which have unknown toxicology.

Customer Service: 800.387.7503 www.cleartech.ca Emergency: 306.664.2522 Page 6 of 9

Skin Very dilute solutions have caused negligible irritation, while more concentrated solutions have caused

acute corrosive injury to skin. Prolonged exposure may lead to permanent scarring of skin.

Ingestion Acute exposure may lead to burning of the mouth and throat, abdominal cramps, nausea, vomiting,

diarrhea, shock. May lead to convulsions, coma, and even death.

Inhalation Causes severe burns to the mouth and throat (mist). May release toxic and irritating chlorine gas.

Chlorine, one of the primary decomposition products of sodium hypochlorite, is an irritant of the nose

and throat, causing coughing, difficulty breathing, and pulmonary edema.

Eye contact Causes irritation, redness, and pain. May cause burns and possible damage to vision.

Sensitization This product and its components at their listed concentration have no known sensitizing effects.

Mutagenicity This product and its components at their listed concentration have no known mutagenic effects.

Carcinogenicity IARC has classified hypochlorite salts as group 3, not classifiable as to its carcinogenicity to humans.

Reproductive toxicity

This product and its components at their listed concentration have no known reproductive effects.

Specific organ toxicity

This product and its components at their listed concentration have no known effects on specific

organs.

Aspiration hazard Prolonged or repeated overexposure may cause lung damage.

Synergistic materials

Not available

Section 12 Ecological Information

Ecotoxicity

Туре	Species	Value	Exposure Time
EC50	Red algea	46 mg/L	96 hours
LC50	Salmo gairdneri	0.07 mg/L	48 hours
LC50	Daphnia magna	0.032 mg/L	48 hours
	EC50 LC50	EC50 Red algea LC50 Salmo gairdneri	EC50 Red algea 46 mg/L LC50 Salmo gairdneri 0.07 mg/L

Biodegradability The domestic substance list categorizes sodium hypochlorite as non-persistent.

Bioaccumulation The domestic substance list categorizes sodium hypochlorite as non-bioaccumulative.

MobilityThis product is water soluble, is not predicted to adsorb to soil and may contaminate ground

water.

Other adverse effects The domestic substance list categorizes sodium hypochlorite as inherently toxic to aquatic

organisms.

Section 13 Disposal Considerations

Waste From Residues / Unused Products

Dispose in accordance with all federal, provincial, and local regulations including the

Canadian Environmental Protection Act.

Contaminated Packaging Do not remo

Do not remove label, follow label warnings even after the container is empty. Empty containers should be recycled or disposed of at an approved waste handling facility.

Section 14 Transport Information

UN number UN 1791

UN proper shipping name

and description

Revision Date: June 11, 2020

HYPOCHLORITE SOLUTION with more than 7% available chlorine

Transport hazard class(es) 8
Packing group III

Customer Service: 800.387.7503 <u>www.cleartech.ca</u> Emergency: 306.664.2522

Page 7 of 9

Excepted quantities

Environmental hazards

Listed as a marine pollutant under Canadian TDG Regulations, schedule III.

5 L

Special precautions

No special provisions

Transport in bulk

ERAP index: not required

MARPOL 73/78 and IBC Code:

Product name: Sodium hypochlorite solution (15% or less)

Pollution category: Y

Hazards: the product is included in the Code because of both its safety

and pollution hazards.

Ship type: ship type 2

Tank type: integral gravity tank Tank vents: controlled venting

Tank environmental control: no special requirements under this Code

Temperature classes no requirements

Electrical equipment: Apparatus group no requirements

> Flash point non-flammable product

Gauging: restricted gauging

Vapour detection: no special requirements under this Code Fire protection: no special requirements under this Code Emergency equipment no special requirements under this Code

Specific and operational 15.19.6 requirements

Additional information

Secure containers (full or empty) during shipment and ensure all caps, valves, or closures are secured in the closed position.

TDG PRODUCT CLASSIFICATION: This product has been classified on the preparation date specified at section 16 of this SDS, for transportation in accordance with the requirements of part 2 of the Transportation of Dangerous Goods Regulations. If applicable, testing and published test data regarding the classification of this product are listed in the references at section 16 of this SDS.

Section 15 Regulatory Information.

NOTE: THE PRODUCT LISTED ON THIS SAFETY DATA SHEET HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CANADIAN HAZARDOUS PRODUCTS REGULATIONS. THIS SAFETY DATA SHEET CONTAINS ALL INFORMATION REQUIRED BY THOSE REGULATIONS.

All components of this product appear on the domestic substance list.

NSF Certification: Hypochlor 12 is certified under NSF / ANSI Standard 60 for disinfection & oxidation at a maximum dosage of: 103 mg/L. NSF product use restrictions based on requirements obtained from the NSF website; consult NSF website for current requirements.

Section 16 Other Information

Date of latest revision: June 11, 2020

Note: The responsibility to provide a safe workplace remains with the buyer / user. The buyer / user should consider the health hazards and safety information contained herein as a guide and should take those precautions required in an individual operation to instruct employees and develop work practice procedures for a safe work environment. The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by the use of this material. It is the responsibility of the buyer / user to comply with all applicable laws and regulations regarding handling, using, reselling and shipping this product.

Customer Service: 800.387.7503 www.cleartech.ca Emergency: 306.664.2522 Revision Date: June 11, 2020

Attention: Receiver of the chemical goods / SDS coordinator

As part of our commitment to the RDC Responsible Distribution® initiative, ClearTech Industries Inc. and its associated companies require, as a condition of sale, that you forward the attached Safety Data Sheet(s) to all affected employees, customers, and end-users. ClearTech will send any available supplementary handling, health, and safety information to you at your request.

If you have any questions or concerns please call our customer service center.

References:

- 1) CHEMINFO
- 2) TOXNET
- 3) eChemPortal
- 4) ECHA
- 5) Transportation of Dangerous Goods Canada
- 6) HSDB
- 7) PAN

Customer Service: 800.387.7503 www.cleartech.ca Emergency: 306.664.2522 Page 9 of 9