# FOAM SLAYER

#### FOAMING CONTROL AGENT

**Earth Pro Foam Slayer** is a versatile, low toxicity blend of products used to control foaming problems in a wide range of applications.

It is very effective in low concentrations and is a more persistent defoamer than alternative defoaming/anti-foaming products.

It is particularly effective in combating foam when drilling through oil sands.

#### **FEATURES & BENEFITS**

- Ideal for combatting mild to severe foaming.
- Can be premixed as an anti-foaming agent in fluids where vigorous agitation is required or with products that are known to have foaming tendencies.
- Easy to mix and works quickly.
- Compatible with other commonly used mud additives.

#### **PHYSICAL PROPERTIES:**

Appearance: Colorless liquid Specific Gravity: 1.005 g/mL Pour Point: -20°C (-4°F) Flash Point: ↑150°C (302°F) - closed cap Viscosity@25°C: 1110 (cST)

## CHEMICAL PROPERTIES:

**Solubility:** Dispersible (water) **Brine:** Dispersible

### MIXING & HANDLING

Defoaming is a complex reaction, therefore, pilot testing may be necessary to determine optimum treatment rates and methods.

DRILLING FLUIDS & ADDITIVES

Recommended treatment concentrations will vary depending on the severity of foaming, however, 0.5-1.5 L/m<sup>3</sup> will be effective in most cases.

For maximum effectiveness, **Earth Pro Foam Slayer** should be added directly to the fluid system, as close to the point to foaming as possible.

WHMIS: Not controlled TDG: Not regulated Packaging: 20L pail



