

BIG BEAR DRILL ROD GREASE®

LUBRICANT

Earth Pro Big Bear Drill Rod Grease® is the world renowned specially thickened drill rod grease with additives that provide corrosion, wear and oxidation resistance.

Tackiness assures adherence to drill rods while providing superior resistance to water washing and centrifugal separation. It possesses the right degree of fibrous characteristics to permit easy application to the drill rods by hand, even in wet conditions.

As the rods are lowered into the drill hole, an adhesive film is formed on the rods that is resistant to the washing action of water or cuttings laden drilling fluid.

This durable grease film will prevent momentary seizure and chattering of the rods or binding in the hole. The frequency of pulling the rods for greasing is reduced and increased drilling costs are avoided.

PROPERTIES:

Appearance: Brownish yellow

Penetration: ASTM

Worked at 25°C: 212

Dropping Point: 252°C (485°F)

Pour Point: -27°C (-15°F)

Viscosity: cSt at 40°C (104°F) is 84.6

cSt at 100°C (212°F) is 7.8

SUS at 40°C (104°C) is 392

SUS at 100°C (212°F) is 52

MIXING & HANDLING

Earth Pro Big Bear Drill Rod Grease® is recommended for grease lubrication on diamond drill rods whether operating on surface or underground.

Packaging: 17kg (34.4 lbs) pail, 36 pails/pallets or approx. 860 pails/20ft seacan

Globally available as Big Bear.
Accept no imposters!

